

Pressure Switch 312200



BARKSDALE_PRESSU_49f07d494c59c.jpg



Single Pressure Switch Adustable 250-3000 PSI

Rating: Not Rated Yet

Price

Sales price \$441.00

Sales price without tax \$441.00

Tax amount

[Ask a question about this product](#)

Description

270000 Hydraulic Pressure Switch. Commonly used on many balers and compactors from 1980-2010. Adjustable from 250-3000psi, proof rated 7000psi, N.O-N.C. contacts rated at 10amp@125v, 1/4" NPT female fluid connection. With mounting bracket and 18" molded leads. Very commonly used on many different hydraulic power units. C9612-3



General Specifications

Electrical Characteristics:	All models incorporate Underwriters Laboratories, Inc. and CSA Listed single pole double throw snap-action switching elements
Accuracy:	±2% of the adjustable range
Switch:	10 amps @ 125, 250, or 480 VAC; 0.03 amps @ 250 VDC, Class B limit switch
Type:	
Rating:	
Wetted Parts:	Nickel plated aluminum
Process Fitting:	Buna-N (standard)
O-ring:	416 stainless steel
Piston:	Anodized aluminum

270000 Baler Pressure Switch

Enclosure:	
Electrical Connection:	18" free leads (terminal block on "T" model)
Enclosure Ratings:	NEMA 3
Pressure Connection:	1/4" - 18 NPT female
Approvals:	UL File E42816
UL/CSA (optional):	Class 3231 02, File No. 022355-0-000
Temperature Range:	-20° to +165°F (-29° to +74°C)
Operating:	-40° to +200°F (-40° to +93°C)
Storage:	
Adjustment Instructions:	With screwdriver, turn adjustment screw counterclockwise to increase and clockwise to decrease the actuation point.
	Barksdale
